

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 683 496 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
16.08.2006 Bulletin 2006/33

(51) Int Cl:
A61B 18/14 (2006.01)

(43) Date of publication A2:
28.07.2006 Bulletin 2006/30

(21) Application number: 06008779.8

(22) Date of filing: 03.06.2003

(84) Designated Contracting States:
DE ES FR GB IE IT

(30) Priority: 06.06.2002 US 164854

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:
03739020.0 / 1 513 464

(71) Applicant: Sherwood Services AG
8200 Schaffhausen (CH)


(72) Inventors:
• Buysse, Steven P.
Longmont, CO 80501 (US)
• Lawes, Kate R.
Superior, CO 80027 (US)

- Schmalz, Dale F.
Fort Collins, CO 80524 (US)
- Lands, Michael J.
Louisville, CO 80027 (US)
- Lukianow, S. Wade
Boulder, CO 80305 (US)
- Johnson, Kristin D.
Louisville, CO 80027 (US)
- Couture, Gary M.
Longmont, CO 80501 (US)
- Nguyen, Lap, P.
Longmont, CO 80501 (US)

(74) Representative: HOFFMANN EITLE
Patent- und Rechtsanwälte
Arabellastrasse 4
81925 München (DE)

(54) Laparoscopic bipolar electrosurgical instrument

(57) A laparoscopic bipolar electrosurgical instrument for sealing tissue includes a handle (14) having an elongated tube (13) affixed thereto and first (15) and second jaw (16) members. Each of the first and second jaw members include an electrically conductive sealing surface (39,40). The opposable sealing surfaces include a non-stick material for reducing tissue adhesion during the sealing process. The first and second jaw members are adapted to connect to a source of electrosurgical energy such that the opposable sealing surfaces are capable of conducting electrosurgical energy through tissue held therebetween. In addition, a stop (90) is disposed on one of the opposable sealing surfaces for maintaining a minimum separation distance between the opposable sealing surfaces; a ratchet (60) is disposed on one of a fixed (50) and a movable (52) handle, and at least one complementary interlocking mechanical interface (62) is disposed on the other of the fixed and movable handles. The ratchet and the complementary interlocking mechanical interface provide at least one interlocking position to maintain a closure force in the range of about 3 kg/cm² to about 16 kg/cm² between opposable sealing surfaces.

**EP 1 683 496 A3**

EP 1 583 496 A3

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 06 00 8779

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

13-06-2006

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5196009	A	23-03-1993	NONE	
US 5391166	A	21-02-1995	NONE	
US 6039733	A	21-03-2000	AU 718528 B2	13-04-2000
			AU 6529396 A	09-04-1997
			CA 2228436 A1	27-03-1997
			EP 0862387 A1	09-09-1998
			WO 9710764 A1	27-03-1997
			JP 10511030 T	27-10-1998
			US 6179834 B1	30-01-2001
			US 5776130 A	07-07-1998

EPO FORM P0038

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82